

FLEXICROP

THE SUPERIOR LAYFLAT HOSE FROM **CCH HOSE**

WIDE RANGING USAGE

- Industry
- Agriculture
- Water transfer, bypass
- Coating of cables and other piping
- Compressed air applications
- Pump exitway
- Construction and civil works
- Ships and supplies

DIAMETER		WEIGHT	THICKNESS	WORKING PRESSURE	BREAKAGE PRESSURE
inches	mm.	gr./m.	mm.	Bars	Bars
3/4"	20	230	2,20	30	>90
7/8"	22	240	2,20	30	>90
1"	25	250	1,95	30	>90
1 1/4"	32	310	2,00	27	>80
1 1/2"	38	345	1,95	21	>62
1 2/3"	42	395	2,10	20	>60
1 3/4"	45	410	1,90	21	>62
2"	52	460	2,00	20	>60
2 1/6"	55	470	2,00	17	>52
2 1/2"	64	600	2,10	17	>52
2 3/4"	70	680	2,30	17	>50
3"	75	790	2,50	17	>50
3 1/4"	80	810	2,25	15	>45
3 1/2"	90	930	2,35	15	>45
4"	102	1030	2,50	17	>52
4 1/3"	110	1160	2,40	15	>45
4 1/2"	115	1180	2,40	10	>30
5"	125	1400	2,70	15	>45
6"	152	1650	2,60	14	>42
8"	204	3100	3,80	14	>42
10"	254	4000	3,90	10	>30
12"	304	4700	3,90	8	>25

CONTACT CCH HOSE & COUPLINGS

01353 722366

CCH's in-house layflat irrigation hose is constructed to provide excellent resistance to abrasion and intensive use. Highly resistant to oil, gasoline and a wide range of chemicals and very resistant to contact and radiant heat, it is a light and flexible hose even at low temperatures (-15°C).

Easy to handle and roll up, Flexicrop is highly resistant to breakage and requires no maintenance or drying.

SUPERIOR CONSTRUCTION

Interior and exterior layer: Specially-formulated in black nitrile rubber and extruded through the circular fabric, its smooth interior wall keeps flow loss to an absolute minimum. Outer grooves improve resistance to abrasion.

Reinforced middle textile: Circular weaved outer layer made from high tenacity polyester thread. No defects (broken threads, knots, etc.).

